

CSD MT Series Drives



INTRODUCTION

- New series of stepping motor drives with EtherCAT interface, now available with a 4th generation firmware release and extended current and voltage range.
- Drives optimized for coupling with SANYO DENKI stepping motors, fitted with encoder, but also able to manage third party motors.
- Also available with other interfaces:

EtherNet/IP EtherCAT

AUTO-FEED

AUTO-FEED is a closed loop function with:

- Very simple tuning
- Lower power consumption and heating



MAIN FEATURES

- Modes of operation: Profile Position, Profile Velocity and Homing.
- Wide range of motor phase current setting and motor current overboost:
 - 120% for CSD ET 94/S4 models
 - 140% for CSD ET S8 models.
- Control of different motors sizes:
 - Up to Nema 24 for CSD ET 94/S4 models
 - Up to Nema 34 for CSD ET S8 models. **NEW!**
- Different variety of HOMING operation modes.
- Encoder feedback and support of different resolution.
- Touch Probe function available.
- Limit switches management.
- 5 + 5 I/Os (MT 94) and 2 + 3 I/Os (MT S4/S8).

CURRENT OVERBOOST +140%



RTA US

AUTO FEED FUNCTION

AUTO SYNC FUNCTION

STO FUNCTION FEATURES

- Safe Torque Off (STO) function - **SIL3**
- Error Detection Monitor

SIL3
SAFE TORQUE OFF (STO)

Please refer to download.rta.it for technical specifications

Series	Model	V _{DC} range (Volt)	I nom. (Amp)	I boost (Amp)	Digital In/Out	STO	Dimensions (mm)
CSD MT	S8 STO	24 to 85	6.0	8.4	2/3	Yes	130x106x32
CSD MT	S4 STO	24 to 48	4.0	4.8	2/3	Yes	130x106x32
CSD MT	94	24 to 48	4.0	4.8	5/5	No	130x106x32

CURRENT OVERBOOST +140%


TECHNICAL FEATURES

- Range of operating voltage:
 - 24-48 VDC for CSD MT 94/S4 models
 - 24-85 VDC for CSD MT S8 models.
- Protections:
 - Protection against under-voltage and over-voltage
 - Protection against a short-circuit at motor outputs
 - Overtemperature protection.
- Electronic damping facility for further acoustic noise and mechanic vibrations reduction.
- Available in plastic boxed version with plug-in connectors.
- Maximum compactness.
- Optoinsulated auxiliary and programmable inputs and outputs.
- Warranty: 24 months.




- A kit for mounting on a DIN rail is available as optional. Code: KNDCGD

POWER AND LOGIC CONNECTIONS



MECHANICAL DIMENSIONS



R.T.A. s.r.l.
Via E. Mattei - Fraz- Divisa
27020 Marcignago (PV) (Italy)
T +39.0382.929.855
F +39.0382.929.150
www.rta.it

R.T.A. Deutschland GmbH
Bublitzer Strasse 34, 40599
Duesseldorf (Germany)
T +49.211.749.668.60
F +49.211.749.668.66
www.rta-deutschland.de

R.T.A. INDIA Pvt LTD
SCMC House, 16/6, 3rd Floor
Vishal Nagar Road - Pimple Nilakh
Pune 411027 - Maharashtra (India)
Tel. +91 9422507445
www.rta-india.in